

PU Adhesive for Wood Bonding

ADHESIVE



DESCRIPTION

Non hazardous, fast curing, flexible solvent free one component adhesive for bonding wood materials.

USES

Lamination of structural beams, finger joints, Glu-Lam, and wood boards

BENEFITS

- ◆ Solvent Free
- ◆ Excellent Temperature Performance
- ◆ Economic
- ◆ Range of curing speeds available
- ◆ Range of viscosities available

PU Adhesive for Wood Bonding

ADHESIVE



PRODUCT SPECIFICATION

Product: Leeson PU Wood Adhesives
Manufacturer: Leeson Polyurethanes Ltd.
Telephone: + 44 (0) 1926 833367

SUBSTRATE REQUIREMENTS

Softwood or hardwood.

PRODUCTS INCLUDED IN THIS SYSTEM

Wide range of products depending on the customers' requirements

Detailed installation instructions are available on request.

IMPORTANT NOTE

Leeson Polyurethanes' products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request.

TECHNICAL INFORMATION

The figures below are typical properties achieved in laboratory tests at 21°C and 55% Relative Humidity

Temperature Resistance

Resistant to temperatures of up to +120°C for long periods.

Chemical Resistance

To various acids, diesel and petrol as well as strong bases.

ENVIRONMENTAL IMPACT

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning.

Environmental and health considerations are controlled during manufacture of the products by Leeson Polyurethanes staff.

FURTHER INFORMATION

To ensure you are specifying a fit for purpose surface for your project please consult our Area Sales Manager for your area or visit our website.

{ A bond for life }